



Falcon F200

Designed to be simple, effective, and efficient, RLE Technologies' F200 monitors environmental parameters and protects facilities from disastrous consequences.

The F200 accepts inputs from four external sensors - you choose whether you'd like to deploy temperature sensors, temperature/humidity sensors, or a combination of the two. An extended leader on the sensors allows you to sample readings from a variety of different points within the vicinity of the F200. From floor to ceiling and corner to corner, you'll know the real-time temperature and humidity within your facility.

Eight digital inputs provide unlimited monitoring possibilities. Use these dry contacts to monitor something as simple as whether a door is opened or closed - handy if you're using the F200 in conjunction with a server cabinet or in a small business application. These digital inputs can also be used to monitor more complex parameters including motion sensors, fire alarms, gas detectors, airflow sensors, and summary alarms from critical equipment including UPSs and generators. You can even use the F200's relay output to control an external device in the event of an alarm condition.

Need leak detection too? We've got you covered. The F200 also includes a single zone leak detection component - it can supervise an SD-Z1 spot detector or up to 200 feet of our patented leak detection sensing cable and inline SD-Z spot detectors.

Once all your monitoring connections are snapped into place, the F200 does the rest. Information is displayed on the F200's sleek, integrated web interface. Intuitive options and menuing keep configuration quick and easy, and the interface can be accessed from any computer or mobile device. The F200 keeps you connected and informed. It provides email notification when environmental conditions exceed acceptable limits, and SNMP and Modbus output protocols allow the data to easily integrate into management systems.

Features

- Simple installation and setup
- Web-accessible with a clean, easy to use, mobile-friendly web interface
- Monitors eight dry contact inputs and four temperature or temperature/humidity sensors, plus one zone of leak detection
- Single zone leak detection supports up to 200' of sensing cable and spot detectors
- USB power - run the F200 from a wall outlet via included adapter or a USB port on a server or other computer
- Multiple alarm notification configurations including audible and visible indicators, integrated web interface, email messaging, and SNMP traps
- Relay output allows for simple control of an external device upon alarm condition
- Modbus output enables simple integration to a Building Management System (BMS)

Benefits

- Plug-and-Play configuration enables quick and effective monitoring of any local or remote facility
- Real-time monitoring, advanced notifications, and customizable thresholds
- Customize the system to suit specific monitoring needs

Available Accessories

- 1-wire digital temperature sensor
- 1-wire digital temperature/humidity sensor
- Leak detection sensing cable

Monitoring & Notification

www.rletech.com

F200 Specifications

| | |
|------------------------------|---|
| Power | (US) 5VDC @ 500mA max.; 110/240VAC 50/60Hz; Wall adapter to USB connector (included) |
| Included Accessories | 3.3ft (1m) network cable, USB power adapter, and USB mini B to USB A cable |
| Wired Inputs | 4 1-wire digital temperature or 1-wire digital temperature/humidity sensor inputs; plug-and-play; configurable alarm points |
| Temperature/Humidity | 8 digital alarm points; configurable |
| Digital (Dry Contact) | One zone leak detection, compatible with all SeaHawk sensing cables and SD-Z and SD-Z1 spot detectors |
| Sensing Cable | 15ft (4.57m) leader cable and EOL (LC-KIT; not included), or wire one SD-Z1 directly to the F200 |
| Cable Input | 200ft (61m) of conductive fluid sensing cable, or 140ft (43m) of chemical sensing cable |
| Maximum Length | |
| Relay Output | 1 Form C summary relay; 2A @ 30VDC, 0.5A @125VAC |
| Alarm Notification | |
| Panel | Audible alarm, visible LED |
| Integrated Web Interface | Dashboard overview with alarm indicators |
| Email | 1 email recipient; email sent on alarm to single recipient, distribution list, or email-to-SMS |
| SNMP Traps | Multiple community strings |
| Web Interface Login Security | 1 password read only, 1 password read/write |
| Communication Port | |
| Ethernet | 10/100 BaseT, RJ45 connector; 500VAC RMS isolation; DHCP enabled; Static IP-addressable |
| Protocols | |
| TCP/IP, HTML, SNMP, NTP | V1; V2C MIB-2 compliant; NMS Manageable with Get and Traps |
| SMTP (email) | SMTP authentication; SMTP relay |
| Modbus TCP/IP | Modbus slave; TCP/IP transmission protocol |
| Operating Environment | |
| Temperature | -40°F to 185°F (-40°C to 85°C) |
| Humidity | 0% to 100% RH, non-condensing |
| Altitude | 15,000ft (4,572m) max. |
| Storage Environment | -40°F to 185°F (-40°C to 85°C) |
| Dimensions | 5.63"W x 1.00"H x 2.63"D (143mmW x 25mmH x 67mmD) |
| Weight | 10.1 oz. (287g) |
| Mounting | Stand alone; keyholes included for wall mount; rack mount bracket available |
| Certifications | CE (pending 9/2013); ETL listed: conforms to UL 61010-1, EN 61010-1; certified to CSA C22.2 NO. 61010-1; RoHS compliant |

